



**LEDBURN CABLES IS  
AN INDEPENDENTLY  
OWNED CABLE  
DISTRIBUTOR.**

## **SFX LOW LOSS COAX FOR EXTENDED DISTANCE**

*This high frequency, low loss cable range is designed to carry CCTV, TV and Satellite signals.*



This high frequency, low loss cable range is designed to carry CCTV, TV and Satellite signals. They are manufactured with gas injected foam which grants the cable a much better mechanical, electrical and ageing performance compared to a solid PE dielectric. This family of cable contains both a foil and braided screen enhancing performance and reducing interference. They are also manufactured with a larger conductor size should further distance be required.

Designed with two larger conductor size options where longer runs are required

- 1.25mm (SFX/125) Available in External PE & Direct Burial
  - 1.65mm (SFX/165) Available in External PE, LSZH & Direct Burial
- SFX125 is stocked on bulk drums therefore we offer a cut to length service.  
Cut to length (multiples of 50m)

# Specification

FX Part Code	Type	Weight	O/D	Central Conductor	Shield	Dialectic	Outer Sheath	Colour	Available Drum Size
<b>SFX/RG11-PVC-BLK</b>	RG11	150	10.3	7/0.40 Cu	PCWB	PE	PVC	Black	1000m, Cut to length
<b>SFX/125-PE-GRN</b>	SFX125	61	8	1.25 Cu	Cu Foil, PCWB	FPE	PE	Black	1000m, Cut to length
<b>SFX/125-DB-GRN</b>	SFX125	82	10.2	1.25 Cu	Cu Foil, PCWB	FPE	DB	Green	1000m, Cut to length